



QuatroStar M3 HO – compact version of QuatroStar HO LED fixture with high intensity RGBW one chip LED engines. Excellent color mixing, high light output makes it a very versatile fixture. 16- bit control mode ensures fine dimming and high refresh rate a flicker free usage.

LIGHT SOURCE	12 CREE MC-E LEDs
PIXELS PER FIXTURE	1, 3
BEAM SPREAD	16°, 22°, 36°, 47°
COLORS	R, G, B, W
AVERAGE COLOR WAVELENGTH	(Red: 625 nm, Green: 530 nm, Blue: 460 nm) White >5700K
REFRESH RATE	1200 Hz
INTENSITY CONTROL	8-bit or 16-bit
CONTROL	DMX 512A + RDM
DMX CHANNELS	3-24
OPERATING VOLTAGE	100-240 VAC 50/60 Hz
POWER CONSUMPTION	200 W
POWER CONNECTORS	Neutrik PowerCON
FUSE	4A 250V
COOLING	Active
OPERATING TEMPERATURE	-20 °C - +40 °C
IP RATING	IP20
FIXING	Adjustable yoke
UNIT DIMENSIONS (WxHxD)	297 x 97 x 136.4 mm
WEIGHT	2.9 kg

QuatroStar M3 HO

QuattroStar M3 HO

DIMENSIONS

