



The LIT6 Mk2 is a compact yet powerful waterproof LED bar, ideal for filling event spaces with ambient light without the need for cables. It also serves as an excellent tool for film lighting applications. The fixture features six high-quality RGBW LEDs and a built-in 99Wh lithium battery, ensuring long-lasting performance. Each LED is individually controllable, offering a full color gamut and precise digital control. The 20° beam angle provides a clean, focused wash of light. The LIT6 Mk2 supports both CRMX and W-DMX control protocols, enabling seamless wireless communication.

SPECIFICATION

LIGHT	
Light Source	6x RGBW chips
Control Modes	1,2,3,6pix (4-32channels)
Lumens	2000 Lumen
Beam Angle	20°
Manual Control	Static, Scene, FX
Features	Variable PWM frequency, Gamma curve, Smart fade
CONNECTIONS	
DMX/RDM	XLR connector IN and THRU
Power In	powerCON TRUE1 compatible
DMX (Wired)	DMX 512A
RDM	Yes
Display	1.3" OLED screen, 4 capacitive buttons
Firmware Update	via DMX link
ELECTRICAL	
Voltage Input	120VAC to 240VAC (50/60 Hz)
Power Consumption	100W max (plugged in)
Inrush Current	<40A
Battery	11.1V/9000mAh/99Wh Li-Ion battery with BMS
LED Power	50W/2h mode, 25W/4h mode, 16W/6h mode, 12W/8h mode, 10W/10h mode, 8W/12h mode
ENVIRONMENT	
Operating Temperature	-25°C to 40°C
Protection Rating	IP65
DIMENSIONS	
Width	330 mm (386.6 mm with yoke)
Height	93mm
Depth	71.3 mm (197.5 mm with yoke)
Weight	3.8 kg
Enclosure Material	Aluminum with black powder coating
Mounting	Adjustable yoke

DIMENSIONS

