



DigiNet MICRO is a bidirectional ArtNet/sACN/ DMX converter with RDM support. Unit features 2 DMX ports that can be assigned to ArtNet/sACN universe. both DMX ports have optical and galvanical isolation. Configuration of the node can be done using built-in web server or DigiNet Manager. The power for DigiNet 2 is provided using PoE (Power over Ethernet) functionality. Screen and navigation pad allows for quick setup and easy maintenance.

ETHERNET PORTS	1
DMX PORTS	2
DMX CONNECTORS	Neutrik XLR5 Female
DMX PORT ISOLATION	Optical, up to 1000 V
DMX CONTROL	DMX 512A+RDM
ETHERNET CONNECTOR	Neutrik EtherCON RJ45
ETHERNET TYPE	10/100 Base-T
NETWORK PROTOCOLS	ArtNet, sACN (E1.31)
ADDITIONAL FEATURES	RDM; HTP merging; easy priority; sACN priority
POWER	24/48 VDC (PoE In)
POWER CONSUMPTION	2.5 W
OPERATING TEMP	-20 to +40 °C
UNIT DIMENSIONS W/PLATE (WxHxD)	84.9 x 145.87 x 51 mm
WEIGHT	0.6 kg

# DigiNet MICRO

# DigiNet MICRO

## DIMENSIONS

