



DigiSwitch 18 makes today's complex show networking easier and accessible for everyone. These simple to operate yet powerful Gigabit Ethernet switches distribute up to five discrete networks – lighting, audio, content, server, console, or communications – quickly, effortlessly, and simultaneously.

- Simultaneously separate and distribute up to five discrete networks – e.g lighting, audio, media, content, console, communications – with a few button presses
- Two EZ-LANs do the work of up to 8 unmanaged Gigabit switches
 - 14 LAN ports in two- and four-port groups, assignable to up to five VLANs
 - 2 EtherCon Trunk ports, 2 OpticalCon Trunk ports (Quad standard. Duo optional)
 - Add a second fibre or copper connection for automatic redundancy and twice the speed Available with 8 ports
 - Compatible with a wide range of entertainment-specific protocols, including AES67, ArtNet, Dante, GreenGo, HippoNet, HogNet, Livewire, MA-Net 2/3, Q-LAN, RAVENNA, RDMNet, sACN, and more!

SPECIFICATION

	Non PoE	PoE
Base TX 10/100/1000 Ports	16	
Fiber Optic Link Ports	2	
Optical Connectors	Neutrik OpticalCON QUAD (DUO option available)	
Ethernet Connectors	Neutrik EtherCON RJ45	
AC Power	100-240V, 50/60Hz	
Power Connector	Neutrik PowerCON TRUE1 IN/THRU	
Number of Ports with PoE	0	8
PoE type	-	"PoE+" (25W) also compatible with "PoE" (15W) devices
PoE standards	-	802.3af and 802.3at
Max unit power consumption	30W	270W
Color LCD display	Yes, 1.8"	
Custom switch configurations	Yes, via LCD menu	
Port status LEDs	Single-color	RGB multicolor
Operating Temperature	-20°C to +40°C	
EIA Rack Units	19" 2U	
Unit Dimensions (WxHxD)	483 x 90 x 305 mm	
Unit Weight	4.9 kg	5.1 kg

DIMENSIONS

