TECHNICAL SPECIFICATIONS – MultiFlash Q+

WEIGHT / DIMENSIONS
Length ....19.7" (500 mm)
Width ....…..6.5" (164 mm)
Height (w/yoke) ....…...10" (257 mm)
Weight ....…..22 lb.(10 kg)

POWER
Operating Voltage 100-240VAC 50/60Hz
Fuse..…..12A 250V slow-blow (5x20 mm)
Power Consumption ....1250 W

LIGHT SOURCE
LEDs... 96 10W RBGW Cree LEDs, divided into 12 segments
Color .... RGBW
Beam spread .... 36°

THERMAL
Max. ambient temperature...+104 °F (+40 °C)
Min. ambient temperature.................…........ ....-13 °F (-25 °C)
Cooling .... air cooled – fan

CONTROL / PROGRAMMING
DMX input .... locking 5-pin XLR male socket
DMX output .... locking 5-pin XLR female socket
DMX pin config. .... pin 1 shield, pin 2 (-), pin 3 (+), pin 4 n/a, pin 5 n/a
Control ....RDM, DMX-512, Demo, Manual mode
DMX Channels – Basic Mode...3, 4, 6, 7, 8
DMX Channels - Advanced Mode............................. 10,12,13,16,19,20,24,25,32,43,56
Power Connector .... Input: PowerCon 20A