



Diginet 416 is a bidirectional ArtNet/sACN-DMX Node with RDM support. Unit features 16 DMX outputs that can be assigned to 4 ArtNet/sACN universes in very convenient way by using switches. All DMX ports have optical and galvanical isolation. Configuration of the node can be done using built-in web server or DigiNet Manager. Gigabit Ethernet allows for this unit to be used in large networks without affecting performance. Large TFT touchscreen allows for quick setup and easy maintenance.

ETHERNET PORTS	1
ARTNET/SACN UNIVERSES	4
DMX PORTS	16
DMX CONNECTORS	Neutrik XLR5 Female
DMX PORT ISOLATION	Optical, up to 1000V
DMX CONTROL	DMX 512A+RDM
ETHERNET CONNECTOR	Neutrik EtherCON RJ45
NETWORK PROTOCOLS	ArtNet, sACN (E1.31)
POWER	100-240V, 50-60 Hz / PoE In (802.3af)
POWER CONNECTORS	Neutrik PowerCON
POWER CONSUMPTION	20W
FUSE	1A 250V
OPERATING TEMPERATURE	-20° to +40° C
MOUNTING	Rack Mount 2U
UNIT DIMENSIONS (WxHxD)	482,6 x 88,1 x 204 mm
WEIGHT	4,2 kg

DigiNet 416

DigiNet 416

DIMENSIONS

